

Description

Background of the Invention

[0001] The technical field of the present invention is ophthalmic surgery and, in particular, instruments for removal of corneal tissue.

[0002] A microkeratome is a medical instrument used for resecting a thin layer of corneal tissue from the surface of the eye. In ophthalmic surgery, microkeratomes are used for various purposes. These purposes include the removal of abnormal growths in the cornea, preparation of damaged eyes for corneal transplants, preparation of eyes for other surgical procedures and direct surgical corrections of refractive disorders.

[0003] Considerable interest has been recently generated in a variety of techniques for reshaping the cornea for refractive vision correction. These techniques are based on the observation that most of an eye's refractive power is contributed by the corneal curvature itself (with the remaining refractive power being provided by the lens of the eye located inside the ocular globe). For people suffering from near-sightedness (myopia), it has been recognized that a slight flattening of the corneal curvature can correct this condition if properly applied. Conversely, correction of far-sightedness (hyperopia) requires a steepening of the corneal curvature. Correction of astigmatism typically requires more complex reprofiling.

[0004] It has been suggested on a number of occasions that it is possible to correct refractive errors by mechanical sculpting of the cornea into an ideal shape and curvature. However, until very recently, there have been no tools suitable for this purpose. The anterior surface of the cornea is covered with a thin layer of epithelial tissue followed by a membrane-like structure known as Bowman's layer. Typically, Bowman's layer is about 30 micrometers thick, although it may vary from as little as 10 micrometers to over 50 micrometers in thickness.

[0005] Below Bowman's layer lies the stroma proper of the cornea. This stromal tissue is approximately 450 micrometers in thickness, although it also varies from individual to individual. Stromal tissue is composed of a highly organized matrix of acellular collagen. The Bowman's membrane that lies above it is less regular and denser.

[0006] Efforts at mechanical sculpting of the cornea have been largely unsuccessful to date because even the sharpest metal (or even diamond) blades are incapable of producing precise ablations of corneal tissue with the necessary accuracy. The irregularity of Bowman's layer is a further complicating factor that has stymied mechanical attempts at wide-area sculpting of the anterior surface of the cornea.

[0007] In an alternative surgical procedure, an anterior segment of the cornea is removed (or partially severed and displaced) by a microkeratome so that the stromal bed can be mechanically sculpted. Because Bow-

man's layer is removed or displaced intact in such procedures, mechanical instruments (e.g., specially designed microkeratomes and the like) have had moderate success in resculpting the stroma proper. After the stromal bed has been surgically reshaped, the anterior lenticule is replaced. Again, this procedure has the advantage of avoiding mechanically shaving Bowman's layer, albeit at the expense of a deeper penetration into the stroma.

[0008] Recently, a new procedure, known as "laser vision correction" has become available to ophthalmologists to perform corneal surgery. Laser vision correction employs high energy pulses of ultraviolet radiation, typically from excimer lasers, to ablate thin layers of corneal tissue by a process known as "photodecomposition." This laser vision correction process relies upon the ability of such laser radiation to remove extremely thin layers of corneal tissue within an exposed area without thermal damage to adjacent tissue. In one type of procedure known as photorefractive keratectomy (PRK), the laser beam is either repeatedly scanned across the cornea or otherwise controlled to expose the cornea to a beam of different shape or size over time so as to effect a cumulative reprofiling of the corneal surface.

[0009] In a particular class of PRK procedures known as Laser Assisted In Situ Keratoplasty (LASIK), a microkeratome is used to remove (or hingedly displace) an anterior lamina of the cornea (in much the same way as in the procedures that involve mechanical sculpting of the stroma) while a laser is used to selectively ablate stromal tissue. Again, like mechanical sculpting procedures, the anterior lamina is replaced following the procedure with Bowman's membrane intact. This LASIK procedure is also very promising but likewise requires precision in the removal of the lamina.

[0010] The microkeratome typically includes an eye ring assembly for placement on the ocular globe such that a portion of the cornea is secured. A cutting blade is then carried along a cutting path defined, at least in part, by the guide ring or other elements connected to the guide ring.

[0011] In ophthalmic surgery, the dimensions of the resection must be very precise and predictable. Precision can depend on several factors, including the pressure exerted by the surgeon's hands on the instrument and on the patient's eye, and the speed at which the blade is pushed to make the resection. Even when the movement of the blade is automated, there are factors that affect the precision of the cut.

[0012] Various techniques have been proposed for improving precision. For example, U.S. Pat. No. 5,980,543 to Carriazo et al. describes a microkeratome having a float arm compressing the surface of a cornea in front of the blade prior to cutting. The float arm is connected to the cutting head to, at least partially, compress the cornea ahead of the blade so as to set the desired thickness of the corneal resection. Carriazo's blade assembly is exemplary of the prior art technique for cou-

pling a blade to the body of the keratome.

[0013] The problem of controlled movement across the guide ring is addressed in U.S. Pat. No. 5,133,726 to Ruiz et al., which discloses a microkeratome with a mechanical drive assembly that provides a uniform mechanical motion. The blade assembly disclosed in Ruiz is introduced into the cavity in such a way that the blade is held parallel to the underside of the upper body of the microkeratome.

[0014] U.S. Patent No. 5,817,115 to Nigam discloses an alternative instrument for making corneal incisions wherein a vacuum holds the cornea in place while an incision is made by a blade sliding through the instrument. The blade is mated to and driven by a plunger which actuates within a recess in the instrument. When the plunger is forced into the instrument, a spring is put in compression thus tending to push the plunger in the direction opposite the plunger's movement. This arrangement purportedly slices the cornea in a single continuous motion.

[0015] There exists a need for better microkeratomes, generally, to facilitate both mechanical and laser vision correction procedures. A better, more accurate keratome, would allow ophthalmic surgeons to perform therapeutic keratectomies (removing small regions of corneal tissue which exhibit abnormal growths or ulcers), resections of anterior corneal segments (as a first step in keratomileusis, stromal sculpting procedures, LASIK procedures and the like) and a variety of other surgical operations on the cornea.

Summary of the Invention

[0016] It has been discovered that unintended movements of the blade assembly occur during use of many microkeratomes and such movements (typically involving a "wobbling" motion of the blade) degrade both the precision and the reproducibility of results. The source of this errant motion can be traced in many instances to the fit of a disposable blade assembly within the microkeratome body. Many commercially available microkeratomes operate with a disposable blade that is intended for use on only one patient. Following each procedure, the blade must be replaced. A conventional design provides for the blade to be bonded to a post that permits easy handling by the clinician. This blade and post assembly is commonly referred to as a "blade assembly." A number of commercially available microkeratomes are designed with a recess into which the blade assembly is placed. Although the assembly is typically designed to fit within the recess, a small amount of clearance is necessary to facilitate insertion and removal of the blade assembly. As a consequence of this clearance, the blade itself is only loosely secured during operation and largely held in place by the pressure exerted against the blade by the corneal tissue during resection.

[0017] Accordingly, methods and devices are dis-

closed to inhibit blade wobbling. In one aspect of the invention, frictional fittings are employed to secure the blade (or blade assembly) within the microkeratome. Various engagement elements are disclosed for immobilizing the post of a blade assembly upon insertion into a microkeratome housing. The engagement elements preferably have spring-like characteristics. By biasing the blade into a secure position, wobbling during usage is substantially lessened if not eliminated.

[0018] In one aspect of the invention, a microkeratome is provided for creating lamellar sections from a biological tissue containing a blade-post assembly and at least one engagement element that improve precision and predictability by preventing undesired blade wobbling.

[0019] In another aspect of the invention, a modified blade assembly is disclosed having a post that is mated to a surgical blade. In one embodiment of the invention, the post can have one or more protrusions that engage at least one side of a recess in the microkeratome thereby creating a frictional fit sufficient to prevent movement of the blade while cutting. For example, the post can bias a portion of the blade assembly against an inner surface of the recess. In another embodiment of the invention, the recess can include certain biasing elements that engage the post to prevent blade wobbling. Further, the post can contain a coupling that permits transverse oscillation of the blade while the engagement element prevents wobbling motions.

Brief Description of the Drawings

[0020] The invention will be more fully understood from the following detailed description taken in conjunction with the accompanying drawings, in which like reference numerals designate like parts throughout the figures, and wherein:

FIG. 1 is a perspective view of a microkeratome in accordance with this invention;

FIG. 2 is a side view of a body portion of the microkeratome of Fig. 1;

FIG. 3 is a side view of a blade assembly in accordance with the invention;

FIG. 4 is a top view of the blade assembly of Fig. 3;

FIG. 5 is a perspective view of an alternative embodiment of a blade assembly in accordance with the invention;

FIG. 6 is another perspective view of an alternative embodiment of a blade assembly in accordance with the invention;

FIG. 7 is yet another perspective view of an alter-

native embodiment of a blade assembly in accordance with the invention;

FIG. 8 is a partially cut away, perspective view of a microkeratome body incorporating an alternative biasing element according to the invention.

Detailed Description of the Drawings

[0021] The features and other details of the invention will now be more particularly described and pointed out in the claims. It will be understood that the particular embodiments of the invention are shown by way of illustration and not as limitations of the invention. The principle features of this invention can be employed in various embodiments without departing from the scope of the invention.

[0022] FIG. 1 illustrates a microkeratome 10 in accordance with the invention that includes a body portion 30, an eye ring assembly 12, and a blade assembly 40. The body 30 is fitted to the eye ring assembly 12 in such a way as to be free to slide across it. The microkeratome 10 also includes a motor 20 or similar drive mechanism. The eye ring assembly 12 can further include a platform 14 that supports and guides the body 30. The body portion 30 further includes a recess 18 that receives a blade assembly 40.

[0023] FIG. 2 is a more detailed description of the microkeratome body 30 having a blade assembly 40 which includes a blade post 42 and a cutting element 50. In accordance with the invention, the blade assembly 40 has an engagement element 44 which biases the blade assembly into a secured position and substantially lessens, if not eliminates, wobbling during usage.

[0024] FIG. 3 shows a side view of the blade assembly having a blade post 42 that is mated to a surgical blade 50 having a blade edge 52. The post has one or more protrusions that engage at least one side of a recess in the microkeratome thereby creating a frictional fit sufficient to prevent movement of the blade while cutting. FIG. 4 shows a top view of a blade assembly 40 having a blade post 42 and a cutting element 50. In this illustration, the blade post has two engagement elements 44A and 44B. The cutting element has a blade edge 52.

[0025] The blade post 42 can also contain a coupling 48 (e.g. to motor 20 of FIG. 1) that permits transverse oscillation of the blade while the engagement element prevents wobbling motions. The blade post 42 can be made from metal. In a further embodiment, the blade post 40 can be a magnetized metal post.

[0026] In use, the eye ring of FIG. 1 (or a similar platform-defining structure) is attached to the eye and the microkeratome body 30 positioned upon it. A blade assembly 40 (with its post 42 and blade 50) is slid into a recess 18 in the body 30. In accordance with the invention, the engagement element 44 secures the blade assembly 40 within the recess 18.

[0027] FIGS. 5-7 show alternative blade assembly

having one or more protrusions that engage at least one side of a recess in the microkeratome thereby creating a frictional fit sufficient to prevent movement of the blade while cutting. In FIG. 5, a blade assembly 40C is shown having an engagement element 44C formed as a horizontal strip, which can be formed by attachment of an elastomeric strip material, or by machining of the part 42 itself. Alternatively, strip 44C can be a magnet or magnetic material. In FIG. 6, a plurality of horizontal biasing strips 44D are provided, e.g., by machining slots in the post 42. In FIG. 7 a plurality of bow shaped engagement elements 44E are shown, which again can be formed by joining one or more biasing elements to the post 42 or by appropriate machining of the post 42.

[0028] FIG. 8 shows a partial view of the body wherein the recess 18 includes certain biasing elements 44F that engage the blade post to prevent wobbling.

[0029] Although a number of engagement elements are illustrated herein, it should be clear that various other mechanisms can be employed to create a frictional fit or otherwise engage the blade within the microkeratome to prevent movement of the blade while cutting. As noted above, the engagement element can be a deformable protrusion. The deformable protrusion can either be on the blade assembly or placed inside the recess itself. In another embodiment, the engagement element is a slot in the post that facilitates deformation of the post upon insertion. The engagement element can also be a plurality of strips or bands. In some applications, it is preferable for the engagement member to exhibit spring-like characteristics (e.g. respond to a compressive force in accordance with the formula: $F = 1/2 K x^2$) while in other applications magnetic or electromagnetic forces can be employed to engage the blade.

Claims

1. A microkeratome for creating lamellar sections from a biological tissue, comprising:

a blade assembly (40) including a blade (50) and a post (42);
a housing (30) comprising a recess (18) for inserting the blade assembly (40); and
at least one engagement element (44) for immobilizing the post (42) of the blade assembly (40) upon insertion into the housing (30)

2. The microkeratome of claim 1, wherein the engagement element (44) biases a portion of the blade assembly (40) against an inner surface of the recess (18).

3. The microkeratome of claim 1, wherein:

the blade (50) has a first surface;
the post (42) is attached to a portion of the first

- surface of the blade (50), the post (42) being dimensioned to substantially correspond to the recess (18) of the microkeratome (10); and the at least one engagement element (44) is associated with the post (42), such that upon insertion of the post (42) and the attached blade (50) into the recess (18), the engagement element (44) abuts at least one interior surface of the recess (18) to confine the post (42) within the recess (18).
4. The microkeratome of any preceding claim, further comprising:
- an eye ring (12) having formed on one surface thereof a series of tracks; and
a motor (20) for driving the blade housing (30) along the tracks on the eye ring (12).
5. A microkeratome for creating lamellar sections from a biological tissue, comprising:
- a blade housing (30) for receiving a blade assembly (40), the housing (30) defining a recess (18) therein;
a blade assembly (40) insertable into the recess (18), the blade assembly (40) including a post (42), a blade (50) and at least one engagement element (44) and dimensioned to substantially correspond to the recess (18) of the blade housing (30);
an eye ring (12) having disposed thereon a plurality of tracks; and
a motor (20) removably connected to the blade housing (30) for driving the blade housing (30) along the tracks on the eye ring (12).
6. A method of removing a lamellar layer of a cornea, comprising:
- attaching an eye ring (12) to an eye;
positioning a microkeratome body (30) on the eye ring (12);
sliding a blade assembly (40) into a recess (18) in the body (30), wherein an engagement element (44) secures the blade holder within the recess (18); and
moving a the blade assembly (40) along the guide ring.
7. A disposable blade assembly (40), comprising:
- a blade (50);
a post (42) attached to a portion of a first surface of the blade (50), the post (42) being dimensioned to substantially correspond to a recess (18) of a microkeratome (10); and
at least one engagement element (44) associated with the post (42), such that upon insertion of the post (42) and the attached blade (50) into the recess (18), the engagement element (44) abuts at least one interior surface of the recess (18) to confine the post (42) within the recess (18).
8. The device of any one of claims 1 to 5 and 7, wherein the engagement element (44) comprises at least one deformable element, preferably a plurality of deformable strips (44E).
9. The device of any one of claims 1 to 5 and 7, wherein the engagement element (44) comprises at least one slot in the post (42) that facilitates deformation of the post (42) upon insertion.
10. The device of any one of claims 1 to 5 and 7, wherein the engagement element (44C) comprises a magnetic material.
11. The device of any one of claims 1 to 5 and 7, wherein the post (42) further comprises a coupling that permits transverse oscillation of the blade (50), the engagement element (44) permitting the oscillation while inhibiting undesired wobbling motions.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7





(11) **EP 1 181 913 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
13.03.2002 Bulletin 2002/11

(51) Int Cl.⁷: **A61F 9/013**

(43) Date of publication A2:
27.02.2002 Bulletin 2002/09

(21) Application number: 01120196.9

(22) Date of filing: 22.08.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:

- **Ritchey, Jr., James L.**
Boxborough, Massachusetts 01719 (US)
- **Gebauer, Detlev**
75233 Tiefenbronn (DE)

(30) Priority: 25.08.2000 US 648668

**(74) Representative: Strehl Schübel-Hopf & Partner
Maximilianstrasse 54
80538 München (DE)**

(71) Applicant: **Alcon Universal, Ltd.**
6331 Hünenberg (CH)

(54) **Microkeratome blade assembly**

(57) The present invention provides a microkeratome 10 for creating lamellar sections from a biological tissue containing a blade-post assembly 40 which improves precision and predictability by preventing undesired blade wobbling. Methods and devices are disclosed to inhibit blade wobbling, preferably frictional fittings are employed to secure the blade 50 (or blade assembly 40) within the microkeratome 10. By biasing the blade 50 into a secure position, wobbling during usage is substantially lessened if not eliminated. A modified blade assembly 40 is disclosed having a post 42

that is mated to a surgical blade 50. In one embodiment of the invention, the post 42 can have one or more protrusions that engage at least one side of a recess 18 in the microkeratome 10 thereby creating a frictional fit sufficient to prevent movement of the blade 50 while cutting. In another embodiment of the invention, the recess 18 can include certain biasing elements that engage the post 42 to prevent blade wobbling. Further, the post 42 can contain a coupling that permits transverse oscillation of the blade 50 while the engagement element 44 prevents wobbling motions.




FIG. 1



European Patent
Office

PARTIAL EUROPEAN SEARCH REPORT

Application Number

which under Rule 45 of the European Patent Convention EP 01 12 0196
shall be considered, for the purposes of subsequent
proceedings, as the European search report

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (InCL7)
X	EP 1 027 873 A (SIS LTD) 16 August 2000 (2000-08-16) * page 3, line 1 - line 5; figures 1-3,5 * * page 1, line 18 - line 57; figure 7 * * page 5, line 42 - line 44 *	1-5,7,9	A61F9/013
A	WO 00 25711 A (INSIGHT TECHNOLOGIES INSTR LLC) 11 May 2000 (2000-05-11)	1-5,9,11	
A	* page 17, line 4 - page 19, line 10; figures 2-5,11 *	7	
X	FR 2 751 206 A (MORIA SA) 23 January 1998 (1998-01-23) * the whole document *	1-5,7,11	
X	WO 00 09055 A (FEINGOLD VLADIMIR) 24 February 2000 (2000-02-24)	1-5	
A	* page 8, line 9 - line 22; figures 6,8A *	7	
X	DE 31 47 662 A (KRUMEICH JOERG DR MED) 9 June 1983 (1983-06-09) * page 8, line 22 - page 9, column 14; figures *	1-3,7,11	TECHNICAL FIELDS SEARCHED (InCL7)
			A61F
INCOMPLETE SEARCH The Search Division considers that the present application, or one or more of its claims, does/do not comply with the EPC to such an extent that a meaningful search into the state of the art cannot be carried out, or can only be carried out partially, for these claims. Claims searched completely : 1-5,7-11 Claims searched incompletely : Claims not searched : 6 Reason for the limitation of the search: Article 52 (4) EPC - Method for treatment of the human or animal body by surgery			
Place of search		Date of completion of the search	Examiner
THE HAGUE		23 January 2002	Wolf, C
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/02 (P4007)

PARTIAL EUROPEAN SEARCH REPORT

Application Number
EP 01 12 0196

DOCUMENTS CONSIDERED TO BE RELEVANT			CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	
A	WO 98 48748 A (HELLENKAMP JOHANN F) 5 November 1998 (1998-11-05) * page 19, line 10 - page 21, line 11; figures 4-6C *	1,4,7	
A	US 5 989 272 A (BARRON MARK B ET AL) 23 November 1999 (1999-11-23) * column 3, line 49 - column 4, line 26; figures 4,5,7 *	1,7	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 12 0196

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

23-01-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1027873	A	16-08-2000	US 6165189 A EP 1027873 A2 JP 2000237229 A	26-12-2000 16-08-2000 05-09-2000
WO 0025711	A	11-05-2000	AU 1343900 A EP 1126804 A2 WO 0025711 A2	22-05-2000 29-08-2001 11-05-2000
FR 2751206	A	23-01-1998	FR 2751206 A1	23-01-1998
WO 0009055	A	24-02-2000	US 6083236 A AU 5347799 A BR 9912927 A EP 1104274 A1 WO 0009055 A1	04-07-2000 06-03-2000 08-05-2001 06-06-2001 24-02-2000
DE 3147662	A	09-06-1983	DE 3147662 A1	09-06-1983
WO 9848748	A	05-11-1998	US 6051009 A AU 7159698 A AU 7259098 A CN 1260701 T CN 1260702 T EP 0977532 A2 EP 1011564 A2 JP 2001517131 T US 6007553 A WO 9848747 A2 WO 9848748 A2 US 6132446 A	18-04-2000 24-11-1998 24-11-1998 19-07-2000 19-07-2000 09-02-2000 28-06-2000 02-10-2001 28-12-1999 05-11-1998 05-11-1998 17-10-2000
US 5989272	A	23-11-1999	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82